

NLS-PT30 Series

1D / 2D CMOS Ruggedized Mobile Computer



The lightweight, multifunctional and ruggedized design of this mobile computer / PDA makes any data collection task a breeze. With its 2.83" sunlight readable screen it can be used in virtually any ambient light condition. In addition, this device boasts a high-speed CPU with the flexible and user-friendly Microsoft Windows CE.NET 6.0 operating system. Data can be stored on the device's 2GB large flash memory or simply transferred via the wireless WiFi / Bluetooth / 3G function. All in all the PT30 series ruggedized PDA is an ideal device for a broad range of indoor as well as outdoor applications.

Product Features

- **High Performance**
Marvell XScale PXA310 806MHz high-speed CPU.
- **Wireless Communication**
Supports WiFi/Bluetooth/GSM/GPRS.
- **Large Memory Capacity**
256MB RAM 128MB ROM, extra 2GB flash memory for user storage area.
- **Industrial Design**
IP54 sealing, 1.2m drop protection.
- **Software Kit for Common Applications** Integrated with many software utilities for common applications, greatly reducing the development cycle and providing convenience for user.
- **Application Protection Mechanism**
Vendor ID Application Protection Mechanism to protect the applications developed by Vendors.

Specifications

Performance		
Processor		Marvell XScale PXA310, 806MHz CPU
Operation System		Microsoft Windows CE.NET 6.0
Memory		256MB RAM
		128MB ROM for system area
		2GB flash memory for user storage
Interface		RS232, USB 2.0, support USB charge
Physical		
Dimensions (L x W x H)		189.5 x 76 x 45 mm (7.5 x 3 x 1.7 inch)
Weight		382g (Including battery)
Display		2.83" QVGA with backlight TFT Touch screen LCD, support sunlight readable
Keyboard		30 Keys Numeric with backlight
Notification		Vibrator, Speaker and LED
Battery	Main	3.7V, 3000mAh Rechargeable Li-Polymer battery
	Backup	3.7V, 150mAh Rechargeable Li-Polymer battery (support 50hours data backup)
Expansion		MicroSD memory slot
Power Adaptor		Output: DC 5V, ≥ 1.5A; Input: AC 100~240V, 50~60Hz
Environmental		
Operation Temperature		-10°C ~ 50°C (14°F~ 122°F)
Storage Temperature		-20°C ~ 60°C (-4°F ~ 140°F)
Humidity		5% ~ 95% (non-condensing)
Static Discharge		±15 kV (Air discharge), ±8 kV (Direct discharge)
Drop		1.2 m drop to concrete
Environmental Sealing		IP54 sealing
Barcode / RFID		
1D Barcode	Laser (≥ 4 mil)	Code128, EAN-13, EAN-8, Code-39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,
	CCD (≥ 4 mil)	ISBN/ISSN, Code 93, etc.
2D Barcode	CMOS (≥ 5 mil)	ALL 1D and PDF-417, QR Code, Data Matrix, Maxicode, Aztec, etc.
Wireless		
WLAN		Summit IEEE 802.11 b/g, security support EAP, WEP, WPA, WPA2, 802.1X
WWAN	3G	WCDMA (850, 900, 1800, 1900, 2100 MHz) or (900, 1800, 1900, 2100 MHz)
WPAN		Bluetooth Class II V2.0
Certificates		
FCC Part15 Class B, CE EMC Class B, CCC		
Accessories		
Cradle, Battery, Adaptor, USB cable, Stylus Pen		

Contact Us:

Newland EMEA
+31 (0) 345 87 00 33
info@newland-id.com

Newland Nordic Branch
+46 (0) 708 847 767
goeran@newland-id.com

Newland South Africa Division
+27 (0) 11 553 8010
info@newland-id.co.za

Newland UK Branch
+44 (0) 1442 212 020
info@newland-id.co.uk

Newland France Branch
+33 (0) 160 707 974
info@newland-id.fr

Newland Middle East Branch
+96 (0) 655 500 9610
shuja.rahman@newland-id.com

Newland Niederlassung D-A-CH
+49 (0) 294 298 76758
info@newland-id.de

Newland Italy Branch
+39 (0) 335 773 0521
cristiano@newland-id.com

Newland Ibérica Branch
+34 (0) 93 303 74 66
info@newland-id.es

www.newland-id.com

Specifications are subject to change without notice.*9

